

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

REMARKS

The above preliminary amendment is made to remove multiple dependencies from claims 4-12, 15, 16, 19 and 21.

A new abstract page is supplied to conform to that appearing on the publication page of the WIPO application, but the new Abstract is typed on a separate page as required by U.S. practice.


Applicants respectfully request that the preliminary amendment described herein be entered into the record prior to calculation of the filing fee and prior to examination and consideration of the above-identified application.

If a telephone conference would be helpful in resolving any issues concerning this communication, please contact Applicants' primary attorney-of record, John J. Gresens (Reg. No. 33,112), at (612) 371.5265.

Respectfully submitted,

MERCHANT & GOULD P.C.  
P.O. Box 2903  
Minneapolis, Minnesota 55402-0903  
(612) 332-5300

Dated: December 12, 2001

By   
John J. Gresens  
Reg. No. 33,112

JJG/pjk

**MARKED-UP COPY OF CLAIMS**

4. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the rotor is provided with a magnetizable material such as soft iron.

5. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the rotor comprises a permanent magnet for contactlessly driving the rotor by means of at least one magnetic field.

6. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the rotor comprises a plurality of arms extending in radial direction of the rotation axis.

7. A dosing device according to claim[s] 5 [and 6], characterized in that the ends of the arms form poles of the permanent magnet.

8. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the pump is driven by the rotor by way of a drive shaft of which an axial axis is directed in a direction from the inlet to the outlet.

9. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the housing of the dosing device is of substantially rotation-symmetrical design, with an axial axis of the housing extending in the direction from the inlet to the outlet.

10. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the dosing device is provided, downstream of the pump, with a valve included in the liquid flow path, which opens when the liquid pressure upstream of the valve exceeds a predetermined threshold valve.

10018232.032602

11. A dosing device according to [any one of the preceding claims] claim 1, characterized in that the pump is constructed as a gear pump.

12. A holder filled with concentrate, which in diluted form, is suitable for consumption, the holder comprises a dosing device according to [any one of the preceding claims] claim 1.

15. A holder according to [any one of] claim[s] 12[-14], characterized in that the housing is of more rigid design than the bag.

16. An apparatus for preparing a beverage suitable for consumption, the apparatus being adapted to be loaded with a holder according to [any one of the preceding] claim[s] 12[-15] which is fitted with a dosing device [according to any one of claims 1-11,] for placement in a dispensing machine which comprises a magnetization unit for generating a changing magnetic field comprising a housing comprising at least one inlet, at least one outlet, a liquid flow path extending from the inlet to the outlet, and a pump included in the liquid flow path, the dosing device being adapted for dispensing in a metered manner a viscous concentrate from a holder in which the concentrate is contained, the concentrate is diluted form giving a product suitable for consumption, the holder comprising a storage space in which the concentrate is contained, and the inlet of the dosing device being adapted to be connected, in use, to the storage space of the holder, characterized in that the dosing device comprises a rotor rotatably connected to the housing for rotation around a rotation axis, for causing the rotor to rotate about the rotation axis by means of the changing magnetic field, the rotor being mechanically connected to the pump for driving the pump with the rotating rotor, the apparatus comprising a magnetization unit for generating at least one magnetic field changing such



magnetization unit for generating at least one magnetic field changing such that the rotor is driven for causing the dosing device to dispense concentrate from the holder.

2025-03-26 10:00:00